

PRODUCT DATA SHEET

PARAPET SEALER

Penetrating Water Repellent

DESCRIPTION:

PARAPET SEALER is a blended silicate solution used to provide resistance to water penetration and water borne contaminants on porous surfaces.

SUGGESTED APPLICATIONS:

PARAPET SEALER is formulated for substrates with a medium to high level of porosity such as:

- Plaster and Concrete Parapets
- All types of plaster
- Face brick
- Cement bricks
- Concrete

CHARACTERISTICS:

PARAPET SEALER is formulated to provide:

- Excellent resistance to water penetration
- Good substrate penetration
- Good ultra-violet resistance
- Fast water repellency
- Dries to a colourless and tack-free film
- Low gloss formation and reduced staining
- May change the colour of the substrate
- Ideally suited to vertical surfaces
- High alkali resistance
- A suitable alternative to plaster primer for quality paints
- May leave a white residue on some substrates
- Does not fill or bridge cracks

APPLICATION INSTRUCTIONS:

- PARAPET SEALER should be applied using a low-pressure airless spray, brush or roller
- Apply a minimum of two coats wet on wet from top to bottom following the 'run'
- Cover all glass and aluminum
- Coverage, depending on the substrate should be between 2 and 6 m² per liter

NOTE:

Substrate to be dry, free of dirt, grease and oils. Avoid pooling and ensure area is well ventilated

MAINTENANCE:

- PARAPET SEALER does not require maintenance
- Product effectiveness should be checked every 10 - 15 years
- Life span can be up to 20 years depending on substrate

NOTE:

PARAPET SEALER like all sealants, is not a permanent indefinite barrier to contaminants therefore all spillages etc. should be removed as soon as possible

STORAGE:

- PARAPET SEALER is stable to reasonable temperature fluctuations
- Shelf life is approximately 1 year
- Store away from direct sunlight in tightly closed, air free containers at 0-20 degrees Celsius
- PARAPET SEALER is classified as hazardous & flammable

DISPOSAL:

Containers should be destroyed by crushing. Do not cut or puncture
Do not use as water carriers

The information in this publication is based on tests that we believe to be reliable. It is the responsibility of the user to ascertain the suitability of the product to the situation since conditions of use are outside of our control and therefore all expressed or implied warranties are confined only to the replacement of product found to be defective upon receipt of goods by purchaser. Written representation for faulty goods must be made to the supplier within 7 days of receipt of product. All products/names are the registered property of SPECKLEEN®

Phone: +27 11 793 3341 Fax: +27 11 793 3342 Mobile: 082 410 6181

E-mail: info@speckleen.co.za | www.speckleen.co.za

4 Retief Place, Northwold, Randburg, Johannesburg, Gauteng, SOUTH AFRICA
P. O. Box 2553 Honeydew, Johannesburg, Gauteng, SOUTH AFRICA, 2040