

PRODUCT DATA SHEET

PERMOSEAL STD WS

Penetrating Spirit Based Fluorocarbon Sealer

DESCRIPTION:

PERMOSEAL STD WS is a blended solvent based fluorocarbon solution used to provide resistance to water and oil borne contaminant on porous surfaces.

SUGGESTED APPLICATIONS:

PERMOSEAL STD WS is formulated for substrates with a medium to low level of porosity such as:

- Polished Granite
- Marble
- Travertine
- Porcelain
- Natural stone where no colour enhancement is a requirement

CHARACTERISTICS:

PERMOSEAL STD WS is formulated to provide:

- Good substrate penetration
- Good oil and water resistance
- Dries to a colourless film
- Low gloss formation
- Suitable for interior and exterior use
- Facilitates easier cleaning even with auto scrubbers
- Reduces staining

APPLICATION INSTRUCTIONS:

- Apply PERMOSEAL STD WS with a brush, roller or similar applicator or low-pressure airless spray allowing approximately 60 minutes drying between coats
- Pooling/running of PERMOSEAL STD WS is to be avoided
- Test an inconspicuous area to assess if tile will absorb more coats before applying additional coats
- Coverage, depending on the substrate should be up to 30 m² per liter per coat

MAINTENANCE:

- PERMOSEAL STD WS should be maintained with SPECKLEEN® cleaners
- It is advisable to remove all wet dirt with a wet extraction machine

STORAGE:

- PERMOSEAL STD WS is stable to reasonable temperature fluctuations
- Shelf life is 1 year
- Do not store or use below 5 degrees celsius
- PERMOSEAL STD WS is classified as hazardous and flammable

DISPOSAL:

- Containers should be punctured on disposal

SAFETY:

- Harmful if swallowed
- If splashed in eyes, wash with copious amounts of water
- Consult a doctor if irritation persists or swallowed

The information in this publication is based on tests that we believe to be reliable. It is the responsibility of the user to ascertain the suitability of the product to the situation since conditions of use are outside of our control and therefore all expressed or implied warranties are confined only to the replacement of product found to be defective upon receipt of goods by purchaser. Written representation for faulty goods must be made to the supplier within 7 days of receipt of product. All products/names are the registered property of SPECKLEEN®

Phone: +27 11 793 3341 Fax: +27 11 793 3342 Mobile: 082 410 6181

E-mail: info@speckleen.co.za | www.speckleen.co.za

4 Retief Place, Northwold, Randburg, Johannesburg, Gauteng, SOUTH AFRICA
P. O. Box 2553 Honeydew, Johannesburg, Gauteng, SOUTH AFRICA, 2040