

## PRODUCT DATA SHEET

# POR

### DESCRIPTION:

POR is a water based slight colour enhancing blended solution used to provide resistance to water and light food oil contaminants on porous surfaces.

### SUGGESTED APPLICATIONS:

POR is formulated as a protective barrier against staining by food oils and beverages, for substrates with a medium to high level of porosity like:

- Stucco plaster
- Moulded concrete
- Off shutter concrete
- Power floated floors
- Cement and concrete tiles

### CHARACTERISTICS:

POR is formulated to provide:

- Good substrate penetration
- Good alkali resistance
- Good resistance to efflorescence & ultra violet
- Dries to a colourless film
- Low gloss formation
- Reduces staining
- Facilitates easier cleaning
- Excellent preventative coating against concrete dusting on vertical off shutter concrete surfaces

### APPLICATION INSTRUCTIONS:

- POR should be applied using a brush, lambswool or similar applicator.
- Apply two-three even coats, allowing approximately 30-60 minutes drying time between coats depending on the ambient temperature.
- Pooling/Running of POR is to be avoided.
- Coverage, depending on the substrate should be up to 30 m<sup>2</sup> per liter.

### MAINTENANCE:

- POR should be maintained with SPECKLEEN® NEUTRADET detergent.
- It is advisable to remove all wet dirt with a wet extraction machine.
- POR like all sealants, is not a permanent indefinite barrier to contaminants therefore all spillages etc. should be removed as speedily as possible.

### STORAGE:

- POR is stable to reasonable temperature fluctuations. Shelf life is approximately 1 year.
- POR is classified as non-hazardous and non-flammable.

### DISPOSAL:

- No special requirements however containers should be punctured on disposal.

### SAFETY:

- Harmful if swallowed.
- If splashed in eyes, wash with copious amounts of water.
- Consult a doctor if irritation persists or swallowed.

*The information in this publication is based on tests that we believe to be reliable. It is the responsibility of the user to ascertain the suitability of the product to the situation since conditions of use are outside of our control and therefore all expressed or implied warranties are confined only to the replacement of product found to be defective upon receipt of goods by purchaser. Written representation for faulty goods must be made to the supplier within 7 days of receipt of product. All products/names are the registered property of SPECKLEEN®*

Phone: +27 11 793 3341 Fax: +27 11 793 3342 Mobile: 082 410 6181

E-mail: [info@speckleen.co.za](mailto:info@speckleen.co.za) | [www.speckleen.co.za](http://www.speckleen.co.za)

4 Retief Place, Northwold, Randburg, Johannesburg, Gauteng, SOUTH AFRICA  
P. O. Box 2553 Honeydew, Johannesburg, Gauteng, SOUTH AFRICA, 2040