

PRODUCT DATA SHEET

STC PUC UV

Colour Enhancing Matt / Gloss Sealer

DESCRIPTION:

STC PUC UV is a hard wearing twin pack urethane solution used to provide resistance to most water and oil borne contaminants on porous surfaces.

Interior/Ext PUC UV For high porosity substrates with a matt - sheen / gloss finish

SUGGESTED APPLICATIONS:

STC PUC UV is formulated as a protective barrier against staining by beverages, light oils / foods, etc., for substrates with a low to high level of porosity such as:

- Slate
- Sandstone
- Terracotta
- Flamed Granite
- Concrete
- Clay tiles

CHARACTERISTICS:

STC PUC UV is formulated to provide:

- Good substrate adhesion
- Hard wearing
- Dries to a colourless film
- Excellent resistance to liquid penetration
- May enhance substrate colour (test first)
- Good ultra violet resistance

NOTE: Substrate to be dry, free of dirt, grease and oils. A damp substrate will result in the coating either delaminating or turning white upon drying. This is almost impossible to remove. Avoid pooling.

MAINTENANCE:

- STC PUC UV should be maintained as and when required using either SPECKLEEN Q500™, SPECKLEEN® NEUTRADET, FLEXCLEAN or ON GUARD.
- Use NO SKIDDING® SRC cleaner for anti slip properties.
- It is advisable to remove all wet dirt with a wet extraction machine.

NOTE: STC PUC UV like all sealants, is not a permanent indefinite barrier to contaminants therefore all spillages etc. should be removed as soon as possible.

STORAGE:

- STC PUC UV is stable to reasonable temperature fluctuations.
- Shelf life is approximately 12 months.
- STC PUC UV is classified as hazardous & flammable and cannot be transported by air.

DISPOSAL:

- Containers should be destroyed by crushing. Do not cut or puncture.

SAFETY:

- Harmful if swallowed, wear protective rubber gloves & organic vapour masks.
- Use in a well ventilated area.
- Do not use if respiratory tract is irritated.
- Active solvent is Xylene and Polyurethane thinner.

The information in this publication is based on tests that we believe to be reliable. It is the responsibility of the user to ascertain the suitability of the product to the situation since conditions of use are outside of our control and therefore all expressed or implied warranties are confined only to the replacement of product found to be defective upon receipt of goods by purchaser. Written representation for faulty goods must be made to the supplier within 7 days of receipt of product. All products/names are the registered property of SPECKLEEN®

Phone: +27 11 793 3341 Fax: +27 11 793 3342 Mobile: 082 410 6181

E-mail: info@speckleen.co.za | www.speckleen.co.za

4 Retief Place, Northwold, Randburg, Johannesburg, Gauteng, SOUTH AFRICA
P. O. Box 2553 Honeydew, Johannesburg, Gauteng, SOUTH AFRICA, 2040