



No Skidding[®]

VULCAN UV

**HIGH PROFILE
ANTI SLIP COATING
FOR PEDESTRIAN TRAFFIC
PRODUCTS NO. 99002 TO 99013**



No Skidding[®]

www.noskidding.com



No Skidding®



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

^{NSP} No Skidding®

VULCAN UV HIGH PROFILE ANTI SLIP COATING

FOR PEDESTRIAN TRAFFIC
PRODUCT NO. 99002 TO 99013

No Skidding® Vulcan UV High Profile Anti Slip Coating is a durable coating that contain special additives to create slip-resistant surfaces. This coating is premixed with the anti slip additive integrated into the product and is easy to apply with either a brush or a roller. This product was developed for moderate to heavy-duty applications around pools, sidewalks, catwalks, boat decks, stairs, ramps, shower rooms or other "slippery when wet" areas.

Description

With its integrated grit, this single component solvent based coating provides a durable anti-slip surface. This non-chlorinated rubber resin coating is formulated for use on new or old concrete surfaces. Its tough anti-slip characteristic reduces slippage on potentially slippery areas. It can be used on flat surfaces inside or outside.

Product Characteristics

- Excellent sure footing even in wet areas like: stairways, loading docks, catwalks, shower rooms, wheel chair ramps, entranceways, swimming pool decks and other potentially slippery surfaces
- Recommended for indoor or outdoor use
- Resistant to alkali, detergents and acids
- A variety of colors are available
- Can be applied to wood, concrete, steel or stone

Technical Data

Weight per Gallon	13 - 14 pounds
Color	Gray 99002, Green 99003, Tile Red 99004, Yellow 99005, Black 99006, Handicap Blue 99007, White 99011
Dry Time	5-6 hours
Flash Point (C.O.C.)	105°F
Coverage	100 sq. ft./gallon

PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

Important: Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.



Method of Application

Surface should be structurally sound and free of water, oil, grease, loose paint, or other soils. Smooth bare concrete should be acid etched to insure good adhesion. Apply with brush, trowel, or notched squeegee. After application, the coating can be back-rolled with a paint roller to level or increase the surface texture.

Use two thin coats for maximum durability. Dry the first coat overnight before applying the second coat. Tools may be cleaned using Rubber Base Thinner. Do not use paint thinner or mineral spirit.

Available Container Sizes

5 Gallon and 1 Gallon Containers

During application, extinguish all flames, including pilot lights, and have adequate ventilation. DO NOT USE IN CLOSED AREA.

The information and data given herein are based upon tests and reports considered reliable and believed to be accurate. However, due to circumstances beyond our control including but not limited to surface preparation, application technique, substrate and curing conditions, no guarantee of duplicate performance, expressed or implied, is made.

No Skidding®



www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&O.E.